



UL LLC
1075 W Lambert Rd Suite B
Brea, CA 92821

Integrating Sphere Test Report

Relevant Standards
IES LM-79-2008, ANSI C82.77-2002, CIE 13.3-1995
CIE 15-2004, ANSI C78.377-2015, IES TM-30-2015

Prepared For
B-K Lighting Inc
Chris McCarthy
40429 Brickyard Dr
Madera, CA 93636-9515
United States

Catalog Number
LBF-LED-X66-SP-9-C
Order Number
11913931
Test Number
11913931.15

Test Date

2017-08-17

Prepared By

Tony Rubio, Technician

Approved By


Eric Gaudreau, Senior Engineering Associate

The results contained in this report pertain only to the tested sample.
This report shall not be reproduced, except in full, without written approval of Underwriters Laboratories.
This report must not be used by the client to claim product certification, approval, or endorsement by
NVLAP, NIST, or any agency of the Federal Government.



Luminaire Description: Formed white metal housing with patterned reflector and clear lens
Lamp: One (1) white LED
Mounting: Pole/Arm
Ballast/Driver: Thomas Research Products LED25W-36-C0700-LE

Luminaire



Summary of Results

Radiant Flux:	7808 mW
Luminous Flux:	2515 lm
Luminaire Efficacy:	93.6 lm/W
CCT:	4162 K
CRI (Ra):	83.5
Chromaticity (x):	0.3732
Chromaticity (y):	0.3712
Chromaticity (u):	0.2225
Chromaticity (v):	0.3320
Duv:	-0.0008

Test Conditions

Test Temperature:	24.3 °C
Voltage:	120.1 VAC
Current:	0.2265 A
Power:	26.86 W
Power Factor:	0.987
Frequency:	60 Hz
Current THD:	12.9 %

Testing was performed in a 3-meter integrating sphere using the 4 π geometry method.
Absorption correction was employed for this measurement.





Color Quality - Integrating Sphere

Integrating Sphere Test Conditions

Temperature	Voltage	Current	Power	Power Factor	Frequency	Current THD
24.3 °C	120.1 VAC	0.2265 A	26.86 W	0.987	60 Hz	12.9 %

Summary of Results

Total Output:	2515 Lumens	Chromaticity (x):	0.3732
Efficacy:	93.6 lm/w	Chromaticity (y):	0.3712
CCT:	4162 K	Chromaticity (u'):	0.2225
CRI (Ra):	83.5	Chromaticity (v'):	0.4980
CRI (R9):	13.9	TM-30 Rf:	82.7
Peak Wavelength:	451.2 nm	TM-30 Rg:	96.2
Dominant Wavelength:	578.7 nm	Duv:	-0.0008
S/P Ratio:	1.733		



Color Rendering Index Detail

Ra (CRI)	R1	R2	R3	R4	R5	R6	R7	R8	R9	R10	R11	R12	R13	R14
83.5	82.0	89.1	93.8	82.6	82.1	84.5	87.0	67.3	13.9	73.5	81.1	64.4	83.6	96.6

