



UL LLC  
1075 W Lambert Rd Suite B  
Brea, CA 92821

## Integrating Sphere Test Report

Relevant Standards  
IES LM-79-2008, ANSI C82.77-2002, CIE 13.3-1995  
CIE 15-2004, ANSI C78.377-2015, IES TM-30-2015

Prepared For  
**B-K Lighting Inc**  
Chris McCarthy  
40429 Brickyard Dr  
Madera, CA 93636-9515  
United States

Catalog Number  
**HLP-LED-e71-WHP-B**  
Order Number  
11717110  
Test Number  
11717110.02

Test Date

2017-04-24

Prepared By

William Escobar, Technician

Approved By

Eric Gaudreau, Senior Engineering Associate

The results contained in this report pertain only to the tested sample.  
This report shall not be reproduced, except in full, without written approval of Underwriters Laboratories.  
This report must not be used by the client to claim product certification, approval, or endorsement by  
NVLAP, NIST, or any agency of the Federal Government.



**Luminaire Description:** White metal shade/reflector, clear plastic lens, and metal base  
**Lamp:** One (1) white LED  
**Mounting:** Ground recessed  
**Ballast/Driver:** Unmarked power supply

**Luminaire**



**Summary of Results**

Radiant Flux:	289.4 mW
Luminous Flux:	94.66 lm
Luminaire Efficacy:	28.3 lm/W
CCT:	2994 K
CRI (Ra):	82.0
Chromaticity (x):	0.4374
Chromaticity (y):	0.4046
Chromaticity (u):	0.2506
Chromaticity (v):	0.3478
Duv:	0.0000

**Test Conditions**

Test Temperature:	24.8 °C
Voltage:	120.2 VAC
Current:	0.05047 A
Power:	3.345 W
Power Factor:	0.552
Frequency:	60 Hz
Current THD:	151 %

Testing was performed in a 2-meter integrating sphere using the 4 $\pi$  geometry method.  
Absorption correction was employed for this measurement.





## Color Quality - Integrating Sphere

### Integrating Sphere Test Conditions

Temperature	Voltage	Current	Power	Power Factor	Frequency	Current THD
24.8 °C	120.2 VAC	0.05047 A	3.345 W	0.552	60 Hz	151 %

### Summary of Results

Total Output:	95 Lumens	Chromaticity (x):	0.4374
Efficacy:	28.3 lm/w	Chromaticity (y):	0.4046
CCT:	2994 K	Chromaticity (u'):	0.2506
CRI (Ra):	82.0	Chromaticity (v'):	0.5217
CRI (R9):	8.8	TM-30 R <sub>f</sub> :	81.6
Peak Wavelength:	606.1 nm	TM-30 R <sub>g</sub> :	97.7
Dominant Wavelength:	582.8 nm	Duv:	0.0000
S/P Ratio:	1.304		



### Color Rendering Index Detail

Ra (CRI)	R1	R2	R3	R4	R5	R6	R7	R8	R9	R10	R11	R12	R13	R14
82.0	80.3	88.8	95.8	80.8	79.9	85.6	84.1	60.7	8.8	73.8	79.5	67.9	82.0	97.5

